


Accurate Environment Monitoring cascading sensors EMD



Full Color Range



High Outlet flexibility and alternating phase



RCM Residual Current Monitoring Option



Hydraulic-magnetic Circuit Breakers monitoring



kWh Metering Accuracy



Secure Locking Outlets



Patented standard C14 plug locking mechanism

### Mechanical features

Ultra light aluminium profile Full adjustable mounting options  
Low profile hydraulic magnetic breakers 10KA 1cn  
C13/C19 combination socket lockable

### Inlet Energy Metering

PDU input energy metering kWh  
PDU input power measurements (W/VA, VAR)  
PDU input (A, V, PF, HZ) measurements  
Circuit breaker monitoring  
Residual current monitoring (optional)  
3 phase balance indicator

### Security Management

Memorylogs for historical data and graphics  
User and alarms thresholds customizable

| Voltage and current | No. of IEX OUTLETS | Item code |
|---------------------|--------------------|-----------|
|---------------------|--------------------|-----------|

|                            |    |                 |
|----------------------------|----|-----------------|
| 230V<br>16A<br><br>1 phase | 12 | IEXPIML601216AH |
|                            | 12 | IEXPIML451216AV |
|                            | 18 | IEXPIML451816AV |
|                            | 24 | IEXPIML452416AV |
|                            | 30 | IEXPIML453016AV |
|                            | 36 | IEXPIML453616AV |
|                            | 42 | IEXPIML454216AV |

|                            |    |                   |
|----------------------------|----|-------------------|
| 230V<br>32A<br><br>1 phase | 12 | IEXCBPIML601232AH |
|                            | 24 | IEXPIMLCB602432AH |
|                            | 12 | IEXCBPIML451232AV |
|                            | 18 | IEXCBPIML451832AV |
|                            | 24 | IEXCBPIML452432AV |
|                            | 36 | IEXCBPIML453632AV |
|                            | 48 | IEXCBPIML454832AV |

|                                  |    |                   |
|----------------------------------|----|-------------------|
| 380 - 415V<br>16A<br><br>3 phase | 12 | IEXPIML601216A3PH |
|                                  | 24 | IEXPIML602416A3PH |
|                                  | 18 | IEXPIML451816A3PV |
|                                  | 24 | IEXPIML452416A3PV |
|                                  | 36 | IEXPIML453616A3PV |
|                                  | 42 | IEXPIML454216A3PV |

|                                  |    |                     |
|----------------------------------|----|---------------------|
| 380 - 415V<br>32A<br><br>3 phase | 12 | IEXCBPIML601232A3PH |
|                                  | 24 | IEXCBPIML602432A3PH |
|                                  | 24 | IEXCBPIML452432A3PV |
|                                  | 36 | IEXCBPIML453632A3PV |
|                                  | 42 | IEXCBPIML454232A3PV |