


Full Color Range



High Outlet flexibility and alternating phase



Hydraulic-magnetic Circuit Breakers metering




P-Lock & V-Lock Compatible outlets

Secure Locking Outlets



kWh +/-1%

kwh Metering Accuracy



Patented standard C14 plug locking mechanism

Mechanical features

Ultra light aluminium profile Full adjustable mounting options
Low profile hydraulic magnetic breakers 10KA 1cn
C13/C19 combination socket lockable

Inlet Energy Metering

PDU input energy metering kWh
PDU input power measurements (WVA)
PDU input (A, V, PF) measurements
Circuit breaker monitoring

Voltage and current	No. of IEX OUTLETS	Item code
---------------------	--------------------	-----------

230V 16A 1 phase	12	IEXPM601216AH
	12	IEXPM451216AV
	18	IEXPM451816AV
	24	IEXPM452416AV
	30	IEXPM453016AV
	36	IEXPM453616AV
	42	IEXPM454216AV

230V 32A 1 phase	12	IEXCBPM601232AH
	24	IEXPMCB602432AH
	12	IEXCBPM451232AV
	18	IEXCBPM451832AV
	24	IEXCBPM452432AV
	36	IEXCBPM453632AV
	48	IEXCBPM454832AV

380 - 415V 16A 3 phase	12	IEXPM601216A3PH
	24	IEXPM602416A3PH
	18	IEXPM451816A3PV
	24	IEXPM452416A3PV
	36	IEXPM453616A3PV
	42	IEXPM454216A3PV

380 - 415V 32A 3 phase	12	IEXCBPM601232A3PH
	24	IEXCBPM602432A3PH
	24	IEXCBPM452432A3PV
	36	IEXCBPM453632A3PV
	42	IEXCBPM454232A3PV