


Accurate Environment Monitoring
cascading sensors EMD



Full Color Range



High Outlet flexibility and alternating phase



RCM Residual Current Monitoring Option



Hydraulic-magnetic Circuit Breakers monitoring



kWh Metering Accuracy
+/-1%




Secure Locking Outlets




Patented standard C14 plug locking mechanism



Field-Replaceable Controller



PDU Cascading Option



Redundant Network Connections



OLED display

Mechanical features

- Ultra light aluminium profile
- Full adjustable mounting options
- Low profile hydraulic magnetic breakers 10KA Icn
- C13/C19 combination socket lockable

Inlet and Outlet Energy Metering

- PDU input energy metering kWh
- PDU input power measurements (WVA, VAR)
- PDU input (A, V, PF, HZ) measurements
- Circuit breaker monitoring
- Residual current monitoring (optional)
- 3 phase balance indicator

Security Management

- Memorylogs for historical data and graphics
- User and alarms thresholds customizable

Voltage and current	No. of IEX OUTLETS	Item code
230V 16A 1 phase	18	IEXPOM501816AV
	24	IEXPOM502416AV
	30	IEXPOM503016AV
	36	IEXPOM503616AV
	42	IEXPOM504216AV

230V 32A 1 phase	12	IEXCBPOM601232AH
	18	IEXCBPOM501832AV
	24	IEXCBPOM502432AV
	36	IEXCBPOM503632AV
	48	IEXCBPOM504832AV

380 - 415V 16A 3 phase	18	IEXPOM501816A3PV
	24	IEXPOM502416A3PV
	36	IEXPOM503616A3PV
	42	IEXPOM504216A3PV

380 - 415V 32A 3 phase	18	IEXCBPOM501832A3PV
	24	IEXCBPOM502432A3PV
	36	IEXCBPOM503632A3PV
	42	IEXCBPOM504232A3PV