




Accurate Environment Monitoring cascading sensors EMD




Energy Efficient Latching Relays



Field-Replaceable Controller



Full Color Range



High Outlet flexibility and alternating phase




Hydraulic-magnetic Circuit Breakers monitoring



kWh Metering Accuracy




OLED display



PDU Cascading Option



RCM Residual Current Monitoring Option



Redundant Network Connections



Secure Locking Outlets

Mechanical features

- Ultra light aluminium profile
- Full adjustable mounting options
- Low profile hydraulic magnetic breakers 10KA 1cn
- C13/C19 combination socket lockable

Inlet and Outlet Energy Metering

- PDU input energy metering kWh
- PDU input power measurements (VA, VAR)
- PDU input (A, V, PF, HZ) measurements
- Circuit breaker monitoring
- Residual current monitoring (optional)
- 3 phase balance indicator

Outlet Control

- Remote On/Off by individual outlet or groups
- Power On/Off delay
- Sequential startup
- User level security assignable
- Individual LED x outlet status indicator

Voltage and current	No. of IEX OUTLETS	Item code
230V 16A 1 phase	18	IEXPOMS501816AV
	24	IEXPOMS502416AV
	30	IEXPOMS503016AV
	36	IEXPOMS503616AV
	42	IEXPOMS504216AV

230V 32A 1 phase	12	IEXCBPOMS601232AH
	18	IEXCBPOMS501832AV
	24	IEXCBPOMS502432AV
	36	IEXCBPOMS503632AV
	48	IEXCBPOMS504832AV

380 - 415V 16A 3 phase	18	IEXPOMS501816A3PV
	24	IEXPOMS502416A3PV
	36	IEXPOMS503616A3PV
	42	IEXPOMS504216A3PV

380 - 415V 32A 3 phase	18	IEXCBPOMS501832A3PV
	24	IEXCBPOMS502432A3PV
	36	IEXCBPOMS503632A3PV
	42	IEXCBPOMS504232A3PV