








The **LG2** rack has been designed to provide users with a high-end solution. Capable of supporting high loads, up to 1500 kg, it is the ideal rack for both IT, cabling and servers.

Strengths

- Universal rack, IT use, servers and cabling.
- Available in various sizes
- Easy assembly, no tools.
 - Aluminium structure and high-strength cast iron corners.
- Maximum load 1500 kg

Color: Black RAL 9005 Textured

LG2 A800 42U F800



Measurement

- Height: 12, 18, 24, 30, 36, 42, 47U
- Width: 600, 800 mm
- Depth: 600, 800, 1000, 1200 mm

Construction

- Assembly
- Delivery in Flatpack (disassembled)
- Optional assembled delivery

Load capacity

- 1500 kg

19" Profiles

- 2 pairs of 19" depth-adjustable fixing profiles

IP protection rating

- IP20 Standard

Colors

- Black RAL 9005

Front Door

- Safety glass with folding handle – cylinder 333
- Optional: hexagonal perforated sheet door, smooth sheet metal and double leaf
- Easy repositioning for right or left opening

- Opening angle 190°

Back door

- Smooth sheet metal door
- With 190° angular aperture
- Optional: glass door, hexagonal perforated sheet door or double leaf door

Side panels

- Removable, using plastic locks

Adjustable feet

- Available wheels (Not included)

Removable openings – Cable entry

- Pre-machined top and bottom openings of 220x72 mm.
- The openings can be covered with plastic blank panels (Not included).
- Number of openings according to size.
- They can also be protected by brushes (Not included)

Ventilation openings

- Number of outlets according to ceiling size
- Number of standard outputs: 4 and 6 openings.

Code	H (U)	Maximum load (kg)	Dimensions (mm)				Doors		Dimensions, including packaging (mm)			Net Weight (kg)
			H1	W	D	Useful depth	Front	Back	H	W	D	
32310312	12	1500	660	600	600	540	PC	PP	810	630	650	28
32310812	12	1500	660	600	800	740	PC	PP	810	630	830	32
32310318	18	1500	926	600	600	540	PC	PP	1075	630	650	36
32310818	18	1500	926	600	800	740	PC	PP	1075	630	830	40
32310324	24	1500	1193	600	600	540	PC	PP	1345	630	650	43
32310243	24	1500	1193	600	1000	940	PC	PP	1345	630	1030	53
32310241	24	1500	1193	600	1000	920	PPH	PPH	1345	630	1030	50
32310330	30	1500	1460	600	600	540	PC	PP	1610	630	630	50
32310830	30	1500	1460	600	800	740	PC	PP	1610	630	830	56
32310336	36	1500	1726	600	600	540	PC	PP	1875	630	650	58
32310836	36	1500	1726	600	800	740	PC	PP	1875	630	830	65
32310342	42	1500	1993	600	600	540	PC	PP	2150	630	650	66
32310842	42	1500	1993	600	800	740	PC	PP	2150	630	830	73
32312642	42	1500	1993	600	800	740	PPH	PPH	2150	630	830	69
32310420	42	1500	1993	600	1000	940	PC	PP	2150	630	1030	80
32310421	42	1500	1993	600	1000	945	PPH	PPH	2150	630	1030	73
32310461	42	1500	1993	600	1000	935	PPH	SPPH	2150	630	1030	82
32310362	42	1500	1993	600	1200	1145	PPH	PPH	2185	800	1200	91
32310462	42	1500	1993	600	1200	1135	PPH	SPPH	2185	800	1200	88
32310847	47	1500	2215	600	800	740	PC	PP	2365	630	830	80
32310470	47	1500	2215	600	1000	940	PC	PP	2365	630	1030	88
32310471	47	1500	2215	600	1000	945	PPH	PPH	2365	630	1030	83
32310386	47	1500	2215	600	1000	935	PPH	SPPH	2365	630	1030	95
32310367	47	1500	2215	600	1200	1145	PPH	PPH	2400	800	1200	85
32310387	47	1500	2215	600	1200	1135	PPH	SPPH	2400	800	1200	92
32311330	30	1500	1460	800	600	540	PC	PP	1610	830	630	60
32311830	30	1500	1460	800	800	760	PC	PP	1610	830	830	66
32312930	30	1500	1460	800	800	740	PPH	PPH	1610	830	830	62
32311342	42	1500	1993	800	600	540	PC	PP	2150	830	630	77
32311842	42	1500	1993	800	800	760	PC	PP	2150	830	830	85
32312942	42	1500	1993	800	800	740	PPH	PPH	2150	830	830	73
32311420	42	1500	1993	800	1000	940	PC	PP	2150	830	1030	92
32311421	42	1500	1993	800	1000	945	PPH	PPH	2150	830	1030	84
32311481	42	1500	1993	800	1000	935	PPH	SPPH	2150	830	1030	87
32311462	42	1500	1993	800	1200	1145	PPH	PPH	2185	800	1200	92
32311482	42	1500	1993	800	1200	1135	PPH	SPPH	2185	800	1200	95
32311847	47	1500	2215	800	800	760	PC	PP	2365	830	830	92
32312947	47	1500	2215	800	800	740	PPH	PPH	2365	830	830	83
32311470	47	1500	2215	800	1000	940	PC	PP	2365	830	1030	104
32311476	47	1500	2215	800	1000	945	PPH	PPH	2365	830	1030	91

32311396	47	1500	2215	800	1000	935	PPH	SPPH	2365	830	1030	94
32311467	47	1500	2215	800	1200	1145	PPH	PPH	2400	800	1200	99
32311397	47	1500	2215	800	1200	1140	PPH	SPPH	2400	800	1200	103

H1: Height in mm without feet, for feet add 28,5-85 mm

Useful depth2: Can vary depending on the set of doors

