







The **SR2** rack has been designed to provide users with an unrivalled balance between price, utility and quality. Ideal for installers and end users who want to spend less time choosing between various utilities.

Strengths

- Universal rack, daily IT use, servers and cabling.
- Available in various sizes
- Pre-configured rack with optional accessories

Color: Black RAL 9005 Textured



SR2 A800 47U F800

Measurement

- Height: 24, 42, 47U
- Width: 600, 800 mm
- Depth: 600, 800, 1000, 1200 mm

Construction

- Assembly

Load capacity

- 1200 kg

19" Profiles

- 2 pairs of 19" depth-adjustable fixing profiles

IP protection rating

- IP20 Standard

Colors

- Black RAL 9005

- Optional: hexagonal perforated sheet door, smooth sheet metal and double leaf
- Easy repositioning for right or left opening
- Opening angle 190°

Back door

- With 190° angular aperture
- Optional: hexagonal perforated sheet door, smooth sheet metal and double leaf

Side panels

- Removable, with lock and sliding latches

Adjustable feet

- Available wheels (Not included)

Ventilation openings

- Number of outlets according to ceiling size
- Number of standard outputs: 4 and 6 openings.
- Available up to 9 fan outlets (Special ceiling not included)

Front Door

- Safety glass with folding handle – cylinder 333

Removable openings – Cable entry

- Pre-machined upper and lower openings. In width 600: 258x68 mm. In width 800: 408x68 mm.
- Openings can be covered with blank panels (Not included).
- They can also be protected by brushes (Not included)

Code	H (in U)	Load rating (kg)	Dimensions (mm)				Doors		Dimensions including packing (mm)			Gross weight (kg)
			H ¹	W	D	Useful depth ²	Front	Rear	H	W	D	
32440324	24	1300	1200	600	600	550	PC	PP	1350	630	650	50
32440024	24	1300	1200	600	600	550	PPH	PPH	1350	630	650	45
32440824	24	1300	1200	600	800	755	PC	PP	1350	630	830	55
32440124	24	1300	1200	600	1000	950	PC	PP	1350	630	1030	60
32440342	42	1300	2000	600	600	550	PC	PP	2150	630	650	75
32440842	42	1300	2000	600	800	755	PC	PP	2150	630	830	83
32440142	42	1300	2000	600	1000	950	PC	PP	2150	630	1030	91
32440442	42	1300	2000	600	1000	950	PPH	PPH	2150	630	1030	83
32440542	42	1300	2000	600	1000	950	PPH	SPPH	2150	630	1030	88
32440742	42	1300	2000	600	1200	1150	PPH	PPH	2185	800	1200	100
32440847	47	1300	2222	600	800	755	PC	PP	2365	630	830	92
32440447	47	1300	2222	600	1000	950	PPH	PPH	2365	630	1030	90
32440747	47	1300	2222	600	1200	1150	PPH	PPH	2400	800	1200	98
32441824	24	1300	1200	800	800	755	PC	PP	1350	830	830	65
32441124	24	1300	1200	800	1000	950	PC	PP	1350	830	1030	71
32441342	42	1300	2000	800	600	550	PC	PP	2150	830	630	88
32441842	42	1300	2000	800	800	755	PC	PP	2150	830	830	96
32441242	42	1300	2000	800	800	755	PPH	PPH	2150	830	830	83
32441142	42	1300	2000	800	1000	950	PC	PP	2150	830	1030	105
32441442	42	1300	2000	800	1000	950	PPH	PPH	2150	830	1030	91
32441542	42	1300	2000	800	1000	950	PPH	SPPH	2150	830	1030	96
32441742	42	1300	2000	800	1200	1150	PPH	PPH	2185	800	1200	100
32441042	42	1300	2000	800	1200	1150	PPH	SPPH	2185	800	1200	104
32441847	47	1300	2222	800	800	755	PC	PP	2365	830	830	108
32441147	47	1300	2222	800	1000	950	PC	PP	2365	830	1030	117
32441447	47	1300	2222	800	1000	950	PPH	PPH	2365	830	1030	98
32441547	47	1300	2222	800	1000	950	PPH	SPPH	2365	830	1030	104
32441947	47	1300	2222	800	1000	950	SPPH	SPPH	2365	830	1030	109
32441747	47	1300	2222	800	1200	1150	PPH	PPH	2400	800	1200	107
32441047	47	1300	2222	800	1200	1150	SPPH	PPH	2400	800	1200	112

H¹: Height in mm without feet, for feet add 28,5-85 mm

Useful depth²: Can vary depending on the set of doors





